

H480C

HARVESTER HEAD



The Waratah H480C harvesting head combines large timber cutting-power with an excellent delimiting quality throughout its diameter range.

Optimized feed force and speed are a result of new feed motor options. 400/630 cc motors provide high performance in early to late thinnings. 500/800[780] cc motors are the preferred choice in late thinnings and regeneration fellings. The H480C gives an unprecedented excellent tree processing performance, especially in large timber. New feed roller arm geometry ensures that feed rollers have solid grip and reliably carry trunks in all diameter ranges. Operators also appreciate the continuous powerful four-wheel feed for efficient feeding with low friction.

New manufacturing processes have led to even more durable frame structures. New tilt frame rubber stoppers protect structures and prolong the frame lifetime. New feed roller arms feature more durable bearings, strengthened cylinders and pins, and well-protected hose routings. Four moving delimiting knives, one fixed top knife, and one fixed bottom knife follow

the contours of the stem. Knife geometry and long cutting edges of the H480C ensure an excellent delimiting quality for all stem diameters.

The proven EVO2 valve provides efficient hydraulic oil flow and head control, and leads to fuel efficiency of the base machine. The SuperCut 100 saw unit has a maximum felling diameter of 710 mm, and can be factory equipped with either Parker or Bucher saw motor options. The saw units' automatic chain tensioning prolong saw bar and chain lifetime, and the integrated chain lubrication ensures economical oil consumption. Daily maintenance has been further simplified, e.g. improved service of the optional color marking system saves time and costs.

 **waratah**
BUILT TO WORK

H480C

HARVESTER HEAD

TECHNICAL DATA

Dimensions:	Width arms open	1880 mm	6.2 ft.
	Width arms closed	1200 mm	4.0 ft.
	Height without rotator and link	1350 mm	4.4 ft.
Weight:	Without rotator and link	1240 kg	2,734 lb.
Felling/Cutting:	Maximum diameter saw cut	710 mm	28.0 in.
	Saw bar	825 mm	32.5 in.
	Bar type	10 mm	.404 in.
	Chain speed (m/s, ft./s)	40 m/s	131 ft./s
Feeding:	4WD with hydraulically driven steel feed rollers		
	Feed force gross		
	With 400/630 cc motors (4xDanfoss)	27 kN	6,070 lbf
	With 500/800 cc motors (4xDanfoss)	30 kN	6,789 lbf
	With 400/630 cc motors (2xDanfoss/2xPoclair)	27 kN	6,070 lbf
	With 500/780 cc motors (2xDanfoss/2xPoclair)	30 kN	6,789 lbf
Speed	4.2–5.3 m/s	14–17 ft./s	
Maximum feed roller opening	680 mm	26.8 in.	
Delimiting:	Delimiting knives	4 moving and 2 fixed	
	Delimiting diameter tip to tip	460 mm	18.1 in.
	Maximum opening upper knives	680 mm	26.8 in.
	Maximum opening lower knives	710 mm	28.9 in.
Hydraulic Requirements:	Maximum operating pressure	28 MPa	4,061 psi
	Recommended pump capacity	290–340 l/min.	77–90 gpm
Control and Measuring System, Adaptation: (assuming the base machine already has a control and measuring system)	Timbermatic H09, 300		
	TimberRite, Motomit IT/PC, Dasa 4		
Control and Measuring System, New Delivery: (systems that can be ordered with the head)	TimberRite		

OPTIONAL EQUIPMENT

- Color marking system, 2 colors:
 - Knife nozzles or Supermark
- Stump treatment system:
 - Saw bar or Nozzles in saw box
- Feed rollers: Moipu, Mense, MTH, V-type MTH, Steel thumbnail, Steel V-profile, Eucalyptus debarking
- Rotator and link
- Rotator valve
- Top knife: fixed wide shape, fixed wave shape, hydraulically activated, Butterfly-knives
- Various types of length measuring wheels
- MTH equipment
- Saw motor: Parker, Bucher
- Chain and saw bar kits
- Tool kits

We reserve the right to amend these specifications at any time without notice. The only warranty provided by Waratah Forestry Attachments is its written Limited Warranty, which accompanies and applies to each product sold by Waratah Forestry Attachments. Waratah disclaims responsibility for liability for any economic loss or personal injury that may occur as a result of any changes to a Waratah product that has not been approved by Waratah as a result of the non-approved inclusion on any Waratah product or any equipment not to Waratah's design or manufacture. Not all products are available in all markets. The manufacturer reserves the right to make changes or add improvements at any time without incurring any obligation to make such changes on machines manufactured previously.

 **waratah**
BUILT TO WORK